

DEPENDENT RESURVEY OF A PORTION OF
THE SUBDIVISIONAL LINES,
T. 35 N., R. 69 E., MDM, NEVADA

CHAINS 40.01	<p>The $\frac{1}{4}$ sec. cor. of secs. 5 and 6, monumented with a sandstone, 17X6X3 ins., firmly set in a mound of earth, showing 4 ins. above ground, plainly mkd. $\frac{1}{4}$ on W. face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R69E S $6\frac{1}{4}$ S 5</p> <p style="text-align: center;">1984</p> <p>Bury the original cornerstone and set a steel fence post, $5\frac{1}{2}$ ft. long, alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. $0^{\circ} 30'$ W., beginning new measurement.</p> <p>Over nearly level land.</p>
9.50	Wash, 20 lks. wide, 2 ft. deep, drains S. 55° E.
38.40	Wash, 20 lks. wide, 4 ft. deep, drains ESE.
42.00	<p>Intersect the Seventh Standard Parallel North.</p> <p>The closing cor. of secs. 5 and 6, monumented with a limestone, 18X10X6 ins., firmly set in a mound of earth, showing 10 ins. above ground, mkd. with 5 grooves on the E. face, 1 groove on the W. face and CC on the S. face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T36N R69E S 31 <hr style="width: 10%; margin: 0 auto;"/>S 6 S 5 T35N R69E CC</p> <p style="text-align: center;">1984</p> <p>Bury the original cornerstone and set a steel fence post, $5\frac{1}{2}$ ft. long, alongside the iron post.</p> <p>From this corner, the standard $\frac{1}{4}$ sec. cor. of sec. 31, T. 36 N., R. 69 E., monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set, showing 4 ins. above ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the Seventh Standard Parallel North, through Range 69 East, executed concurrently under this same Group, bears S. $89^{\circ} 16'$ E., 1.55 chs. dist.</p>