

DEPENDENT RESURVEY OF THE SEVENTH STANDARD
PARALLEL NORTH, THROUGH RANGE 69 EAST,
MDM, NEVADA

CHAINS	
	Over nearly level land, covered with scattered sagebrush.
1.17	The N. $\frac{1}{4}$ sec. cor. of sec. 5, T. 35 N., R. 69 E., monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set showing 4 ins. above ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the subdivisional lines of T. 35 N., R. 69 E., executed concurrently under this same Group.
39.62	<p>The standard $\frac{1}{4}$ sec. cor. of sec. 31, monumented with a quartz stone, 16X10X8 ins., mkd. with SC and $\frac{1}{4}$ on the N. face, firmly set 6 ins. in the ground.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> SC T36N R69E $\frac{1}{4}$ S 31 <hr style="width: 10%; margin: 0 auto;"/> 1984 </div> <p>Deposit the original cornerstone and set a steel fence post, $5\frac{1}{2}$ ft. long, alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. $89^{\circ} 16'$ W., beginning new measurement.</p> <p>Over nearly level land.</p>
1.55	The closing cor. of secs. 5 and 6, T. 35 N., R. 69 E., monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set showing 4 ins. above ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the subdivisional lines of T. 35 N., R. 69 E., executed concurrently under this same Group.
3.50	Wash, 10 lks. wide, 2 ft. deep, drains SE.
39.50	Wash, 20 lks. wide, 2 ft. deep, drains SE.
40.31	<p>The standard cor. of Tps. 36 N., Rs. 68 and 69 E., monumented with a limestone, 20X8X6 ins., mkd. with 6 grooves on the N., E. and W. faces and SC on the N. face, firmly set 6 ins. in the ground.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>