

DEPENDENT RESURVEY OF THE SEVENTH STANDARD
PARALLEL NORTH, THROUGH RANGE 69 EAST,
MDM, NEVADA

CHAINS

SC
T36N
R68E R69E
S 36 | S 31

1984

Deposit the original cornerstone and set a steel fence post, 5½ ft. long, alongside the iron post.

DEPENDENT RESURVEY OF THE EAST BOUNDARY,
T. 36 N., R. 69 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey Executed by U.S. Deputy Surveyors J. C. Smyles and C. S. Preble, in 1881 and
The Resurvey by Compassman H. Thurtell, in 1903, and the retracement of a portion of the East Boundary by U.S. Surveyor N. E. Potter, in 1914.

From the standard cor. of Tps. 36 N.; Rs. 69 and 70 E.

N. 0° 01' E., bet. secs. 31 and 36.

Over mountainous land, covered with scattered sagebrush and juniper.

- 7.60 Ridge, bears NE. and SW.
19.20 Ridge, bears WSW. and E.
21.20 Ravine, drains WSW.
24.20 Ridge, bears E. and W.
35.00 Ridge, bears E. and W.
38.20 Ravine, drains W.
39.60 The ¼ sec. cor. of secs. 31 and 36, monumented with a limestone, 14X12X8 ins., plainly mkd. ¼ on W. face, firmly set 3 ins. in the ground.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to top, with brass cap mkd.