

DEPENDENT RESURVEY OF THE EAST BOUNDARY,  
T. 36 N., R. 69 E., MDM, NEVADA

CHAINS		
	<p style="text-align: center;">T36N R69E R70E <math>\frac{1}{4}</math> S 12   S 7  1984</p>	
57.00	Ravine, drains W.	
72.90	Ridge, bears WNW. and ESE.	
78.70	<p>Point for the cor. of secs. 1, 6, 7 and 12, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 10 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T36N R69E R70E S 1   S 6 S 12   S 7  1984</p>	
	<hr/> <p>N. <math>0^{\circ} 08'</math> E., bet. secs. 1 and 6.</p> <p>Over mountainous land, covered with juniper and pinon pine.</p>	
8.20	Ravine, drains W.	
25.90	Ridge, bears E. and W.	
39.36	<p>The <math>\frac{1}{4}</math> sec. cor. of secs. 1 and 6, monumented with a quartzite stone, 18X10X4 ins., plainly mkd. <math>\frac{1}{4}</math> on W. face, firmly set 4 ins. in the ground.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T36N R69E R70E <math>\frac{1}{4}</math> S 1   S 6  1984</p> <p>Deposit the original cornerstone and set a steel fence post, <math>5\frac{1}{2}</math> ft. long, alongside the iron post.</p> <p>From this corner, a spring draining NW., bears N. <math>40^{\circ} 30'</math> W., 18.86 chs. dist.</p> <hr/>	