

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 36 N., R. 69 E., MDM, NEVADA

CHAINS	
	Over gently rolling land.
7.70	Wash, 10 lks. wide, 3 ft. deep, drains W.
31.40	Wash, 20 lks. wide, 10 ft. deep, drains W.
34.30	Wash, 10 lks. wide, 4 ft. deep, drains W.
40.54	The cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., firmly set in a mound of stone, with brass cap mkd. as described in the field notes of T. 37 N., R. 69 E., executed concurrently under this same Group.
	From the standard cor. of secs. 33 and 34, on the S. bdy. of the Tp.
	N. 0° 01' W., bet. secs. 33 and 34.
	Over nearly level land, covered with scattered sagebrush.
5.70	Wash, 80 lks. wide, 3 ft. deep, drains SW.
21.50	Wash, 20 lks. wide, 1 ft. deep, drains WSW.
23.90	Wash, 30 lks. wide, 4 ft. deep, drains SW.
40.26	Point for the ¼ sec. cor. of secs. 33 and 34, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T36N R69E ¼ S 33 S 34 1984
	Set a steel fence post, 5½ ft. long, alongside the iron post.
56.30	Wash, 30 lks. wide, 2 ft. deep, drains, W.
76.00	Wash, 30 lks. wide, 4 ft. deep, drains W.
80.52	Point for the cor. of secs. 27, 28, 33 and 34, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to top, with brass cap mkd.
	T36N R69E S 28 S 27 S 33 S 34 1984