

DEPENDENT RESURVEY OF THE EAST BOUNDARY,
T. 37 N., R. 69 E., MDM, NEVADA

CHAINS	
	<p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T37N R69E R70E ¼ S 12 </p> <p style="text-align: center;">1984</p> <p>Deposit the original cornerstone and set a steel fence post, 5½ ft. long, alongside the iron post.</p> <p>From this corner, a fence corner, bears EAST, 0.15 chs. dist., from which fences bear N. and S.</p> <hr/> <p>N. 0° 32' E., beginning new measurement.</p> <p>Over rolling land.</p>
17.40	Wash, 10 lks. wide, 1 ft. deep, drains WSW.
32.10	Wash, 10 lks wide, 1 ft. deep, drains WSW.
39.65	<p>The original closing cor. of secs. 6 and 7, T. 37 N., R. 70 E., monumented with a granite stone, 16X14X10 ins., firmly set in a mound of stone in a fence corner, from which fences bear S. and W., plainly mkd. with 1 groove on N. face and 5 grooves on S. face, bears EAST, 0.03 chs. dist.</p>
41.27	<p>The cor. of secs. 1 and 12, monumented with a granite stone, 20X18X12 ins., firmly set 4 ins. in the ground, plainly mkd. with 1 groove on N. face and 5 grooves on S. face.</p>
	<p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T37N R69E R70E S 1 S 6 S 12 </p> <p style="text-align: center;">1984</p> <p>Deposit the original cornerstone and set a steel fence post, 5½ ft. long, alongside the iron post.</p> <hr/> <p>N. 0° 47' E., along the E. bdy. of sec. 1.</p> <p>Over rolling land, covered with white sage and shadscale.</p>