

DEPENDENT RESURVEY OF THE WEST BOUNDARY,
T. 37 N., R. 69 E., MDM, NEVADA

CHAINS		
40.58	<p>Deposit the original cornerstone and reset the steel fence post alongside the iron post.</p> <hr/> <p>N. 0° 01' W., beginning new measurement.</p> <p>Over rolling land.</p> <p>The cor. of secs. 6 and 7, monumented with a mound of stone, with a steel fence post, 30 ins. long, firmly set in the mound of stone. This point correlates well with other existing original corners and is accepted as the best available evidence of the position of the original corner. (Record wooden post.)</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T37N R68E R69E S 12 S 6 S 7</p> <p style="text-align: center;">1984</p> <p>Reset the steel fence post alongside the iron post and rebuild the mound of stone, 3 ft. base, 2 ft. high, E. of cor.</p>	
3.10 35.00 40.75	<p>N. 0° 22' W., along the W. bdy. of sec. 6.</p> <p>Over rolling land, covered with white sage and shadscale.</p> <p>Trail road, bears E. and W.</p> <p>Wash, 10 lks. wide, 1 ft. deep, drains ENE.</p> <p>Point for the W. ¼ sec. cor. of sec. 6, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T37N R68E R69E ¼ S 6</p> <p style="text-align: center;">1984</p> <p>Set a steel fence post, 5½ ft. long, alongside the iron post.</p>	
70.60	<p>Trail road, bears NE. and SW.</p>	