DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY, T. 32 N., R. 33 E., MDM, NEVADA

	T. 32 N., R. 33 E., MDM, NEVADA
CHAINS	DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY, T. 32 N., R. 33 E., MOUNT DIABLO MERIDIAN, NEVADA
	Reestablishment of the Survey Executed by E. H. Dyer, U.S. Deputy Surveyor, in 1863, the Resurvey Executed by F. H. Criss, U.S. Deputy Surveyor, in 1901 and J. R. Munson, Cadastral Surveyor, in 1974 and the Investigation Survey Executed by C. S. Swanholm, U.S. Surveyor, in 1919 and 1920.
	From the standard $\frac{1}{4}$ sec. cor. of sec. 35, monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set and showing 6 ins. above ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the south boundary, T. 32 N., R. 33 E., executed under Group No. 498. This corner will now also refer to the NW. cor. of sec. 35, T. $31\frac{1}{2}$ N., R. 33 E.
	Brass cap remarked
	SC T32N R33E $\frac{1}{4}$ S 35 T31 $\frac{1}{2}$ N R33E S 35
	1983 1974
	N. 88° 36' E., on the S. bdy. of sec. 35.
	Over mountainous land, covered with scattered juniper, shadscale and native grass.
24.50	Ridge, bears NW. and SE.
27.70	Ravine, drains NW.
31.30	Ridge, bears N. and S.
37.50	Ravine, drains N. 20° E.
39.24	The closing cor. of secs. 35 and 36, T. $31\frac{1}{2}$ N., R. 33 E., hereinafter described.
39.70	Spur, slopes N.
40.41	The standard cor. of secs. 35 and 36, monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set in a mound of stone, with brass cap mkd. as described in the field notes of the dependent resurvey of the south boundary, T. 32 N., R. 33 E., executed under Group No. 498. Add the marks 1984 to the brass cap.