DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY, T. 32 N., R. 33 E., MDM, NEVADA

_			
	chains 19.90	Ravine, drains NW.	
	27.30	Top of ridge, bears N. 20° E. and S. 20° W.	
	35.30	Ravine, drains NE.	
	37.53	The standard closing cor. of sec. 36, monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set and showing 6 ins. above ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the south boundary, T. 32 N., R. 33 E., executed under Group No. 498.	
		From this corner, the SW. cor. of sec. 31, T. 32 N., R. 34 E., monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set in a mound of stone, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the south boundary, T. 32 N., R. 34 E., executed under Group No. 491, bears S. 1° 37' W., 3.10 chs. dist.	
		From this same corner, the W. \(\frac{1}{4}\) sec. cor. of sec. 31, T. 32 N., R. 34 E., monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set and showing 6 ins. above ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the west boundary, T. 32 N., R. 34 E., executed under Group No. 491, bears N. 1° 37' E., 35.94 chs. dist.	
		DEPENDENT RESURVEY OF THE SOUTH BOUNDARY, T. 31½ N., R. 33 E., MOUNT DIABLO MERIDIAN, NEVADA	
		Reestablishment of the Resurvey Executed by H. B. Maxson, U.S. Deputy Surveyor, in 1893 and the Investigation Survey Executed by Carl S. Swanholm, U.S. Surveyor, in 1919 and 1920.	
		From the standard $\frac{1}{4}$ sec. cor. of sec. 35, T. 32 N., R. 33 E. and the NW. cor. of sec. 35, T. $31\frac{1}{2}$ N., R. 33 E., hereinbefore described.	
		N. 89° 52' E., on the S. bdy. of sec. 35.	
		Over mountainous land, covered with scattered juniper, sagebrush, shadscale and native grass.	
	9.44	The closing cor. of secs. 1 and 2, T. 31 N., R. 33 E., monumented with an aluminum post, $2\frac{1}{2}$ ins. diam., firmly set and showing 6 ins. above ground, with aluminum cap mkd. as described in the field notes of the dependent and independent resurvey of a portion of the subdivisional lines, T. 31 N., R. 33 E., executed concurrently under this same Group.	
	39.23	The Maxson standard cor. of secs. 35 and 36, T. 32 N., R. 33 E., and as identified in the 1919 and 1920 investigation survey, monumented with a quartzite stone, 18X10X7 ins., firmly set in a mound of stone, plainly mkd. with 5 grooves on the W. face and no other marks found. This corner now refers to secs. 35 and 36, T. $31\frac{1}{2}$ N., R. 33 E.	