

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY,
T. 31½ N., R. 33 E., MDM, NEVADA

CHAINS	
	<p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T31½N R33E S 35 S 36 ----- S 1 T31N R33E</p> <p style="text-align: center;">1983</p> <p>Deposit the original cornerstone alongside the aluminum post and raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p>
	<p>S. 89° 23' E., on the S. bdy. of sec. 36.</p>
	<p>Over mountainous land, covered with scattered juniper, sagebrush, shadscale and native grass.</p>
8.78	<p>The N. ¼ sec. cor. of sec. 1, T. 31N., R. 33 E., monumented with an aluminum post, 2½ ins. diam., firmly set and showing 6 ins. above ground, with aluminum cap mkd. as described in the field notes of the dependent and independent resurvey of a portion of the subdivisional lines, T. 31 N., R. 33 E., executed concurrently under this same Group.</p>
10.20	<p>Humboldt Canyon, with creek in bottom, 10 lks. wide, 6 ft. deep, course NW.</p>
15.30	<p>Road, bears N. 60° W. and S. 60° E.</p>
30.80	<p>Spur, slopes SSW.</p>
39.50	<p>The Maxson standard ¼ sec. cor. of sec. 36, T. 32 N., R. 33 E., and as identified in the 1919 and 1920 investigation survey, monumented with a granite stone, 18X10X6 ins., firmly set in a mound of stone, plainly mkd. ¼ on the N. face. This corner now refers to the S. ¼ sec. cor. of sec. 36, T. 31½ N., R. 33 E.</p>
	<p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T31½N R33E ¼ S 36 ----- T31N R33E</p> <p style="text-align: center;">1983</p> <p>Deposit the original cornerstone alongside the aluminum post and raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 88° 21' E., beginning new measurement.</p> <p>Over mountainous land.</p>