DEPENDENT RESURVEY OF THE EAST BOUNDARY, T. 31 N., R. 33½ E., MDM, NEVADA

3, Humboldt No. 2 lode, both of M.S. No. 419 monumented with an aluminum post, 2½ ins. 41 firmly set and showing 6 ins. above ground, aluminum cap mkd. as described in the field of the dependent resurvey, of T. 31 N., R. 3 executed concurrently under this same Group, N. 88° 47' W., 4.451 chs. dist. Cor. No. 3 of M.S. No. 4195, Humboldt lode, monumented with an aluminum post, 2½ ins. di firmly set in a mound of stone, with aluminu mkd. as described in the field notes of the dependent resurvey, T. 31 N., R. 33 E., exec concurrently under this same Group, bears S. 47' E., 7.658 chs. dist. Continuing measurement, on the E. bdy. of sec. 6. 33.00 Stream in Humboldt Canyon, 20 lks. wide, 1 ft. de course NW. 36.58 Point for the E. ½ sec. cor. of sec. 6, determine EAST of the ½ sec. cor. of secs. 1 and 6, Tps. 31 Rs. 33 and 33½ E., to an intersection with this 1 Set an aluminum post, 30 ins. long, 2½ ins. diam. ins. in the ground, with aluminum cap mkd. T31N R33½E R34E ½ 5 6 1983 Raise a mound of stone, 3 ft. base, 2 ft. high, W cor. From this corner, the Criss closing cor. of secs. 7, T. 31 N., R. 34 E., and also identified in the and 1920 investigation survey, monumented with a granite stone, 17x9x8 ins., firmly set in a mound stone, plainly mkd. with 5 grooves on the S. face groove on the N. face, bears S. 0° 52' W., 3.87 c dist. 39.15 The Criss E. ½ sec. cor. of sec. 1, Tp. 31 N., R. E., and also identified in the 1919 and 1920 investigation survey, monumented with a granite s 27x16x9 ins., firmly set in a mound of stone, pla mkd. ½ on the W. face. This corner now becomes a	·	T. 31 N., R. 33½ E., MDM, NEVADA
monumented with an aluminum post, 2½ ins. difirmly set in a mound of stone, with aluminum kd, as described in the field notes of the dependent resurvey, T. 31 N., R. 33 E., exec concurrently under this same Group, bears S. 47' E., 7.658 chs. dist. Continuing measurement, on the E. bdy. of sec. 6. 33.00 Stream in Humboldt Canyon, 20 lks. wide, 1 ft. de course NW. 36.58 Point for the E. ½ sec. cor. of sec. 6, determine EAST of the ½ sec. cor. of secs. 1 and 6, Tps. 31 Rs. 33 and 33½ E., to an intersection with this 1 Set an aluminum post, 30 ins. long, 2½ ins. diam. ins. in the ground, with aluminum cap mkd. T31N R33½ E R34E ½	CHAINS	
Stream in Humboldt Canyon, 20 lks. wide, 1 ft. de course NW. 36.58 Point for the E. & sec. cor. of sec. 6, determine EAST of the & sec. cor. of secs. 1 and 6, Tps. 31 Rs. 33 and 33% E., to an intersection with this 1 Set an aluminum post, 30 ins. long, 2% ins. diam. ins. in the ground, with aluminum cap mkd. T31N R33% ER34E		monumented with an aluminum post, 2½ ins. diam., firmly set in a mound of stone, with aluminum cap mkd. as described in the field notes of the dependent resurvey, T. 31 N., R. 33 E., executed concurrently under this same Group, bears S. 88°
course NW. Point for the E. & sec. cor. of sec. 6, determine EAST of the & sec. cor. of secs. 1 and 6, Tps. 31 Rs. 33 and 33½ E., to an intersection with this 1 Set an aluminum post, 30 ins. long, 2½ ins. diam. ins. in the ground, with aluminum cap mkd. T31N R33½E R34E		Continuing measurement, on the E. bdy. of sec. 6.
EAST of the ½ sec. cor. of secs. 1 and 6, Tps. 31 Rs. 33 and 33½ E., to an intersection with this 1 Set an aluminum post, 30 ins. long, 2½ ins. diam. ins. in the ground, with aluminum cap mkd. T31N R33½E R34E ½ S 6 1983 Raise a mound of stone, 3 ft. base, 2 ft. high, W cor. From this corner, the Criss closing cor. of secs. 7, T. 31 N., R. 34 E., and also identified in the and 1920 investigation survey, monumented with a granite stone, 17x9x8 ins., firmly set in a mound stone, plainly mkd. with 5 grooves on the S. face groove on the N. face, bears S. 0° 52' W., 3.87 c dist. 39.15 The Criss E. ½ sec. cor. of sec. 1, Tp. 31 N., R. E., and also identified in the 1919 and 1920 investigation survey, monumented with a granite s 27x16x9 ins., firmly set in a mound of stone, pla mkd. ½ on the W. face. This corner now becomes a angle point on the boundary bet. secs. 6 and 6, T N., Rs. 33½ and 34 E.	33.00	Stream in Humboldt Canyon, 20 lks. wide, 1 ft. deep, course NW.
ins. in the ground, with aluminum cap mkd. T31N R33½E R34E	36.58	Point for the E. ½ sec. cor. of sec. 6, determined due EAST of the ½ sec. cor. of secs. 1 and 6, Tps. 31 N., Rs. 33 and 33½ E., to an intersection with this line.
R33½E R34E 1983 Raise a mound of stone, 3 ft. base, 2 ft. high, W cor. From this corner, the Criss closing cor. of secs. 7, T. 31 N., R. 34 E., and also identified in the and 1920 investigation survey, monumented with a granite stone, 17X9X8 ins., firmly set in a mound stone, plainly mkd. with 5 grooves on the S. face groove on the N. face, bears S. 0° 52' W., 3.87 c dist. 39.15 The Criss E. ½ sec. cor. of sec. 1, Tp. 31 N., R. E., and also identified in the 1919 and 1920 investigation survey, monumented with a granite s 27X16X9 ins., firmly set in a mound of stone, pla mkd. ½ on the W. face. This corner now becomes a angle point on the boundary bet. secs. 6 and 6, T N., Rs. 33½ and 34 E.		Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.
R33½E R34E 1983 Raise a mound of stone, 3 ft. base, 2 ft. high, W cor. From this corner, the Criss closing cor. of secs. 7, T. 31 N., R. 34 E., and also identified in the and 1920 investigation survey, monumented with a granite stone, 17X9X8 ins., firmly set in a mound stone, plainly mkd. with 5 grooves on the S. face groove on the N. face, bears S. 0° 52' W., 3.87 c dist. 39.15 The Criss E. ½ sec. cor. of sec. 1, Tp. 31 N., R. E., and also identified in the 1919 and 1920 investigation survey, monumented with a granite s 27X16X9 ins., firmly set in a mound of stone, pla mkd. ½ on the W. face. This corner now becomes a angle point on the boundary bet. secs. 6 and 6, T N., Rs. 33½ and 34 E.		T 21 N
Raise a mound of stone, 3 ft. base, 2 ft. high, W cor. From this corner, the Criss closing cor. of secs. 7, T. 31 N., R. 34 E., and also identified in the and 1920 investigation survey, monumented with a granite stone, 17x9x8 ins., firmly set in a mound stone, plainly mkd. with 5 grooves on the S. face groove on the N. face, bears S. 0° 52' W., 3.87 c dist. 39.15 The Criss E. ½ sec. cor. of sec. 1, Tp. 31 N., R. E., and also identified in the 1919 and 1920 investigation survey, monumented with a granite s 27x16x9 ins., firmly set in a mound of stone, pla mkd. ½ on the W. face. This corner now becomes a angle point on the boundary bet. secs. 6 and 6, T N., Rs. 33½ and 34 E.		R33½E R34E
From this corner, the Criss closing cor. of secs. 7, T. 31 N., R. 34 E., and also identified in the and 1920 investigation survey, monumented with a granite stone, 17X9X8 ins., firmly set in a mound stone, plainly mkd. with 5 grooves on the S. face groove on the N. face, bears S. 0° 52' W., 3.87 c dist. 39.15 The Criss E. ½ sec. cor. of sec. 1, Tp. 31 N., R. E., and also identified in the 1919 and 1920 investigation survey, monumented with a granite s 27X16X9 ins., firmly set in a mound of stone, pla mkd. ½ on the W. face. This corner now becomes a angle point on the boundary bet. secs. 6 and 6, T N., Rs. 33½ and 34 E.		1983
7, T. 31 N., R. 34 E., and also identified in the and 1920 investigation survey, monumented with a granite stone, 17X9X8 ins., firmly set in a mound stone, plainly mkd. with 5 grooves on the S. face groove on the N. face, bears S. 0° 52' W., 3.87 c dist. 39.15 The Criss E. ½ sec. cor. of sec. 1, Tp. 31 N., R. E., and also identified in the 1919 and 1920 investigation survey, monumented with a granite s 27X16X9 ins., firmly set in a mound of stone, pla mkd. ½ on the W. face. This corner now becomes a angle point on the boundary bet. secs. 6 and 6, T N., Rs. 33½ and 34 E.		Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
E., and also identified in the 1919 and 1920 investigation survey, monumented with a granite s 27X16X9 ins., firmly set in a mound of stone, pla mkd. 4 on the W. face. This corner now becomes a angle point on the boundary bet. secs. 6 and 6, T N., Rs. 33½ and 34 E.		granite stone, 17X9X8 ins., firmly set in a mound of stone, plainly mkd. with 5 grooves on the S. face and 1 groove on the N. face, bears S. 0° 52' W., 3.87 chs.
At the corner point	39.15	investigation survey, monumented with a granite stone, 27X16X9 ins., firmly set in a mound of stone, plainly mkd. a on the W. face. This corner now becomes an angle point on the boundary bet. secs. 6 and 6, Tps. 31
		At the corner point