DEPENDENT RESURVEY OF THE EAST BOUNDARY, T. 31 N., R. 33 E., MDM, NEVADA

CHAINS

39.15

Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with aluminum cap mkd.

1983

Deposit the decayed remains of the original wooden post alongside the aluminum post and raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.

Cor. No. 3, Humboldt lode, hereinbefore described, bears S. 88° 47' E., 10.35 chs. dist.

35.30 Trail road, bears NW. and SE.

38.60 Steam in Humboldt Canyon, 20 lks. wide, 1 ft. deep, course NW.

The $\frac{1}{4}$ sec. cor. of secs. 1 and 6, Tps. 31 N., Rs. 33 and 34 E., established by the 1893 survey and identified in the 1919 and 1920 investigation survey, monumented with a mound of stone. No mkd. stone found. This position is harmoniously related to other existing original corners and the investigation survey of 1919 and 1920 and is accepted as the original corner. This corner now becomes the $\frac{1}{4}$ sec. cor. of secs. 1 and 6, Tps. 31 N., Rs. 33 and $33\frac{1}{2}$ E.

At the corner point

Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T31N
R33E R33 $\frac{1}{2}$ E $\frac{1}{4}$ S 1|S 6

1983

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

N. 0° 35' E., beginning new measurement.

Over mountainous land.

Intersect the S. bdy. of sec. 36, T. $31\frac{1}{2}$ N., R. 33 E.

Point for the closing cor. of secs. 1 and 6, Tps. 31 N., Rs. 33 and $33\frac{1}{2}$ E.

40.00