

DEPENDENT AND INDEPENDENT RESURVEY OF A PORTION OF
THE SUBDIVISIONAL LINES,
T. 31 N., R. 33 E., MDM, NEVADA

CHAINS
39.58

The $\frac{1}{4}$ sec. cor. of secs. 1 and 2, established by the 1893 survey and identified by the 1919 and 1920 investigation survey, monumented with a granite stone, 18X8X8 ins., firmly set in a mound of stone, dimly mkd. $\frac{1}{4}$ on the W. face.

At the corner point

Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T31N R33E

$\frac{1}{4}$
S 2|S 1

1983

Deposit the original cornerstone alongside the aluminum post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

N. $2^{\circ} 50'$ E., beginning new measurement.

Over mountainous land.

38.50

Intersect the S. bdy. of sec. 35, T. $31\frac{1}{2}$ N., R. 33 E.

Point for the closing cor. of secs. 1 and 2.

Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T $31\frac{1}{2}$ N R33E

S 35
S 2|S 1

T31N R33E

C C

1983

Raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.

From this corner, the closing cor. of secs. 1 and 2, established by the 1893 survey and identified by the 1919 and 1920 investigation survey, monumented with a quartzite stone, 17X13X7 ins., firmly set in a mound of stone, plainly mkd. with 5 grooves on the W. face, 1 notch on the E. edge and CC on the S. face, bears N. $2^{\circ} 50'$ E., 1.42 chs. dist. This corner now becomes an amended monument. Add the marks AM and bury the original cornerstone.