

DEPENDENT AND INDEPENDENT RESURVEY OF A PORTION OF
THE SUBDIVISIONAL LINES,
T. 31 N., R. 33 E., MDM, NEVADA

<p>CHAINS 40.20</p>	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 2, at proportionate distance based on the 1863 survey; there is no remaining evidence of the original corner. This corner now refers to sec. 3 only.</p> <p>Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T31N R33E $\frac{1}{4}$ S 3 </p> <p style="text-align: center;">1983</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p>
<p>41.64</p>	<p>The W. $\frac{1}{4}$ sec. cor. of sec. 37, hereinafter described.</p>
<p>59.90</p>	<p>Improved gravel road, bears WNW. and ESE.</p>
<p>80.82</p>	<p>The cor. of secs. 2, 3 and 37, hereinbefore described.</p>
<p>81.27</p>	<p>Intersect the S. bdy. of sec. 34, T. 32 N., R. 33 E.</p> <p>Point for the closing cor. of secs. 2 and 3, T. 31 N., R. 33 E.</p> <p>Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T32N R33E S 34 S 3 S 2 T31N R33E C C</p> <p style="text-align: center;">1983</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.</p> <p>From this corner, the standard $\frac{1}{4}$ sec. cor. of sec. 34, T. 32 N., R. 33 E., monumented with an iron post, 1 in. diam., firmly set in a mound of stone, with brass cap mkd. as described in the field notes of the dependent resurvey of the South boundary, T. 32 N., R. 33 E., executed under Group No. 498, bears N. $89^{\circ} 21'$ W., 8.91 chs. dist.</p> <p>From this same corner, the standard sec. cor. of secs. 34 and 35, T. 32 N., R. 33 E., monumented with an iron post, 3 ins. diam., firmly set in a mound of stone, with brass cap mkd. as described in the field notes of the dependent resurvey of the south boundary, T. 32 N., R. 33 E., executed under Group No. 498, bears S. $89^{\circ} 21'$ E., 30.87 chs. dist.</p>