

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,  
T. 34 N., R. 54 E., MDM, NEVADA

CHAINS

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

T34N R54E

$$\frac{1}{4} \frac{S \ 34}{S \ 3}$$

T33N

1984

Set a steel fence post,  $5\frac{1}{2}$  ft. long, alongside the iron post.

---

N.  $89^{\circ} 39'$  W., beginning new measurement.

Over rolling land.

35.50 Wash, 20 lks. wide, 4 ft. deep, drains S.

40.22 The cor. of secs. 3, 4, 33 and 34, monumented with a willow post, 2 ins. square, 14 ins. long, with illegible scribe marks visible, firmly set alongside a sandstone, 10X8X5 ins. plainly mkd. with 3 grooves on E. and W. faces, firmly set and exposed 6 ins. above the ground, in a fence bearing N. and S.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

T34N R54E

$$\frac{S \ 33 \ | \ S \ 34}{S \ 4 \ | \ S \ 3}$$

T33N

1984

Reset the original wooden post and deposit the cornerstone alongside the iron post.

---

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,  
T. 34 N., R. 54 E., MOUNT DIABLO MERIDIAN, NEVADA

---

Reestablishment of the Survey Executed by  
U.S. Deputy Surveyors A. Craven and J. E. Gignoux  
in 1878 and by U.S. Deputy Surveyor H. B. Maxson,  
in 1896.

---