

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
T. 34 N., R. 54 E., MDM, NEVADA

<p>CHAINS 38.90</p>	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 13 and 18, at proportionate distance; there is no remaining evidence of the original corner. This corner now refers to the $\frac{1}{4}$ sec. cor. of sec. 13, only.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T34N R54E R54$\frac{1}{2}$E $\frac{1}{4}$ S 13 </p> <p style="text-align: center;">1984</p> <p>Set a steel fence post, $5\frac{1}{2}$ ft. long, alongside the iron post.</p>
57.10	Wash, 10 lks. wide, 2 ft. deep, drains E.
57.20	Trail road, bears WNW. and ESE.
65.00	Wash, 10 lks. wide, 2 ft. deep, drains E.
77.29	<p>The closing cor. of secs. 12 and 13, T. 34 N., R. 54$\frac{1}{2}$ E., monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set and exposed 4 ins. above the ground, with brass cap mkd. as described in the field notes of the survey of the subdivisional lines of T. 34 N., R. 54$\frac{1}{2}$ E., executed concurrently under this same Group.</p>
77.80	<p>The cor. of secs. 7, 12, 13 and 18, monumented with a granite stone, 10X10X6 ins. loosely set in a mound of stone, plainly mkd. with 4 grooves on S. face and 2 grooves on N. face. This corner now refers to the cor. of secs. 12 and 13, only.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T34N R54E R54$\frac{1}{2}$E S 12 S 12 S 13 </p> <p style="text-align: center;">1984</p> <p>Deposit the original cornerstone and set a steel fence post, $5\frac{1}{2}$ ft. long, alongside the iron post.</p>
	<p>N. 5° 50' E., along the E. bdy. of sec. 12.</p> <p>Over rolling land, covered with scattered sagebrush and cheatgrass.</p>
13.70	Fence, bears NW. and SE.
26.00	Wash, 10 lks. wide, 2 ft. deep, drains SE.