DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 33 N. R. 55 E. MDM. NEVADA

T. 33 N., R. 55 E., MDM, NEVADA		
	CHAINS	N. 0° 27' W., beginning new measurement.
		Over rolling land.
	1.50	Trail road, bears NE. and SW.
	36.70	The cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp., monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set in a mound of stone, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the south boundary of T. 34 N., R. 55 E., executed concurrently under this same Group.
		From the cor. of secs. 8, 9, 16 and 17.
		N. 86° 50' W., bet. secs. 8 and 17.
		Over rolling land, covered with scattered sagebrush, cheatgrass and juniper, along fence.
	1.00	Ravine, drains NW.
	39.97	The $\frac{1}{4}$ sec. cor. of secs. 8 and 17, monumented with a granite stone, 10X6X4 ins., plainly mkd. $\frac{1}{4}$ on N. face, firmly set alongside a wooden post, 4 ins. square, 30 ins. long in a fence, bearing E. and W.
		At the corner point
		Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
		T33N R55E 1 S 8 S 17
		1984
		Deposit the original cornerstone alongside the iron post.
		y oc° /ol v besiming and more than
		N. 86° 49' W., beginning new measurement.
	00.00	Over rolling land.
	23.30	Trail road, bears NW. and SE.
	37.53	The cor. of secs. 7, 8, 17 and 18, monumented with a basalt stone, 22X10X8 ins., plainly mkd. with 4 grooves on the S. face and 5 grooves on the E. face, firmly set alongside a wooden post, 3 ins. square, 18 ins. long, at the corner of fence, from which fences bear S. and E.
		At the corner point