

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,
T. 31 N., R. 56 E., MDM, NEVADA

CHAINS	
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<div>T32N R56E</div> <div><div><div>½</div><div>S 33</div></div><div><div>S 4</div></div></div> <div>T31N</div> <div>1974</div> <div>1983</div>
	<div>N. 87° 24' W., beginning new measurement.</div> <div>Over rolling land.</div>
0.10	Fence, bears S. and N., 4.70 chs. to fence cor., from which fences bear S. and E.
15.40	Fence, parallels paved road.
17.20	Paved road, bears N. 75° W. and S. 75° E.
18.40	Fence, parallels paved road.
39.75	Point for the cor. of secs. 4, 5, 32 and 33, determined latitudinally at proportionate distance and longitudinally by an old fence bearing N. and S., falls in creek, 8 lks. wide, 6 ins. deep, course NW.; there is no remaining evidence of the original corner.
	Point selected for the witness cor. of secs. 4, 5, 32 and 33, bears N. 0° 47' W., 0.29 chs. dist.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<div>W C</div> <div>T32N R56E</div> <div><div><div>S 32</div><div>S 33</div></div><div><div>S 5</div><div>S 4</div></div></div> <div>T31N</div> <div>1974</div> <div>1983</div>
	Set a steel fence post, 5½ ft. long, alongside the iron post.
	From true point for the corner, the cor. of Tps. 31 and 32 N., Rs. 55 and 56 E., monumented with a willow post, 2 ins. diam., 12 ins. long, plainly scribed RVVI T XXXI N, alongside a steel fence post, 5 ft. long, bears N. 87° 24' W., 161.27 chs. dist.
	At the corner point