

DEPENDENT RESURVEY OF A PORTION OF THE  
SUBDIVISIONAL LINES,  
T. 31 N., R. 57 E., MDM, NEVADA

CHAINS	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<div>T31N R57E</div> <div><div><div>1/4</div><div>S</div><div>5</div></div><div><div>S</div><div>8</div></div></div> <div>1981</div> <div>1983</div>
	<div>N. 89° 45' W., beginning new measurement.</div> <div>Over nearly level land.</div>
7.00	Trail road, bears N. and S.
40.75	The cor. of secs. 5, 6, 7 and 8.
	<div>S. 89° 56' W., bet. secs. 6 and 7.</div> <div>Over nearly level land, covered with scattered sagebrush.</div>
3.70	Creek, 5 lks. wide, 1 ft. deep, course N. 40° W.
15.20	Trail road, bears N. 80° E. and S. 80° W.
25.50	Fence, bears N. 46° W. and S. 46° E.
25.80	Improved gravel road, bears N. 46° W. and S. 46° E.
39.70	Point for the ¼ sec. cor. of secs. 6 and 7, at proportionate distance; there is no remaining evidence of the original corner.
	<div>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground to solid rock and in a mound of stone, 2½ ft. base to top, with brass cap mkd.</div> <div><div>T31N R57E</div><div><div><div>1/4</div><div>S</div><div>6</div></div><div><div>S</div><div>7</div></div></div><div>1981</div></div> <div>Set a steel fence post, 5½ ft. long, alongside the iron post.</div>
80.20	The cor. of secs. 1, 6, 7 and 12, monumented with an iron post, 2½ ins. diam., firmly set and exposed 12 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the E. bdy. of T. 31 N., R. 56 E., executed concurrently under this same Group.