## DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 31 N., R. 57 E., MDM, NEVADA

From the cor. of secs. 5, 6, 7 and 8.  N. 0° 33' E., bet. secs. 5 and 6.  Over nearly level land, covered with scattered sagebrush.  1.70 Creek, 5 lks. wide, 6 ins. deep, course W.  3.90 Trail road, bears, on curve, from S. 70° E. to S. 70° W.  39.30 Fence, bears E. and W.  39.81 The ½ sec. cor. of secs. 5 and 6, at the corner of fences bearing N. and W. This fence cor. is locally recognized and is accepted as the best available evidence of the position of the original corner.  At the corner point  Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.  T31N R57E  \$ 6   \$ 5  1981 1983
Over nearly level land, covered with scattered sagebrush.  1.70 Creek, 5 lks. wide, 6 ins. deep, course W.  3.90 Trail road, bears, on curve, from S. 70° E. to S. 70° W.  39.30 Fence, bears E. and W.  39.81 The ½ sec. cor. of secs. 5 and 6, at the corner of fences bearing N. and W. This fence cor. is locally recognized and is accepted as the best available evidence of the position of the original corner.  At the corner point  Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.  T31N R57E  \$ 6   S 5  1981
sagebrush.  1.70 Creek, 5 lks. wide, 6 ins. deep, course W.  3.90 Trail road, bears, on curve, from S. 70° E. to S. 70° W.  39.30 Fence, bears E. and W.  39.81 The ½ sec. cor. of secs. 5 and 6, at the corner of fences bearing N. and W. This fence cor. is locally recognized and is accepted as the best available evidence of the position of the original corner.  At the corner point  Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.  T31N R57E  \$ 6   S 5  1981
3.90 Trail road, bears, on curve, from S. 70° E. to S. 70° W.  39.30 Fence, bears E. and W.  39.81 The ½ sec. cor. of secs. 5 and 6, at the corner of fences bearing N. and W. This fence cor. is locally recognized and is accepted as the best available evidence of the position of the original corner.  At the corner point  Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.  T31N R57E  ½ S 6 S 5
39.30 Fence, bears E. and W.  39.81 The \( \frac{1}{4} \) sec. cor. of secs. 5 and 6, at the corner of fences bearing N. and W. This fence cor. is locally recognized and is accepted as the best available evidence of the position of the original corner.  At the corner point  Set an iron post, 28 ins. long, 2\frac{1}{2} ins. diam., 24 ins. in the ground, with brass cap mkd.  T31N R57E  \$ 6 \section 5  1981
The ½ sec. cor. of secs. 5 and 6, at the corner of fences bearing N. and W. This fence cor. is locally recognized and is accepted as the best available evidence of the position of the original corner.  At the corner point  Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.  T31N R57E  24  S 6   S 5  1981
fences bearing N. and W. This fence cor. is locally recognized and is accepted as the best available evidence of the position of the original corner.  At the corner point  Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.  T31N R57E  \[ \frac{1}{4} \] S 6   S 5  1981
Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.  T31N R57E $\frac{1}{4}$ S 6   S 5
in the ground, with brass cap mkd.  T31N R57E  \[ \frac{1}{4} \] S 6   S 5  1981
s 6 s 5
1981
N. 0° 33' E., beginning new measurement.  Over nearly level land.
19.96 Point for the N. 1/16 sec. cor. of secs. 5 and 6.
Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
T31N R57E
N 1/16 S 6 S 5
1981 1983
Cor. is located 2 lks. W. of a fence, bearing N. and S., along fence.
The cor. of secs. 5, 6, 31 and 32, on the N. bdy. of the Tp.
SUBDIVISION OF A PORTION OF SECTION 3, T. 31 N., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA