

DEPENDENT RESURVEY OF THE EAST BOUNDARY,
T. 39 N., R. 62 E., MDM, NEVADA

CHAINS	Bury the original cornerstone and set a steel fence post, 5½ ft. long, alongside the iron post.
	<p>N. 0° 47' E., bet. secs. 1 and 6.</p> <p>Over rolling land, covered with sagebrush and native grass, along fence.</p>
35.00	Bench top, bears E. and W.
40.10	<p>The ¼ sec. cor. of secs. 1 and 6, determined latitudinally at proportionate distance and longitudinally in a fence bearing N. and S.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T39N R62E R63E ¼ S 1 S 6 1984</p> <p>Set a steel fence post, 5½ ft. long, alongside the iron post.</p>
	<p>N. 0° 41' E., beginning new measurement.</p> <p>Over rolling land, along fence.</p>
5.20	Top of bench, bears E. and W.
12.00	Creek, 10 lks. wide, 1 ft. deep, course E.
25.70	Johnson Creek, 100 lks. wide, 3 ft. deep, course SE.
39.59	<p>The cor. of Tps. 39 and 40 N., Rs. 62 and 63 E., monumented with a redwood post, 4 ins. square, 30 ins. long, wired to a fence corner, from which fences bear N., S., E. and W., plainly mkd. with 6 notches on the N., S., E. and W. edges and with illegible scribe marks visible on 4 sides.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T40N R62E R63E S 36 S 31 S 1 S 6 T39N 1984</p>