

DEPENDENT RESURVEY OF A PORTION OF
THE WEST BOUNDARY,
T. 39 N., R. 62 E., MDM, NEVADA

CHAINS		
	<p>Bury the original wooden post alongside the iron post.</p> <hr/> <p>N. 0° 14' E., bet. secs. 1 and 6.</p> <p>Over rolling land, covered with sagebrush and native grass, along fence.</p>	
16.80	Fence corner, from which fences bear N., S. and E.	
40.16	<p>The $\frac{1}{4}$ sec. cor. of secs. 1 and 6, monumented with a mound of stone in a corner of fences bearing S. and E. No mkd. stone found. This point correlates well with other existing original corners and is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T39N R61E R62E $\frac{1}{4}$ S 1 S 6 1984</p> <hr/> <p>N. 1° 42' E., beginning new measurement.</p> <p>Over rolling land.</p>	
35.86	<p>The cor. of Tps. 39 and 40 N., Rs. 61 and 62 E., monumented with a granite stone, 15X10X3 ins., firmly set 8 ins. in the ground, plainly mkd. with 6 notches on the N., S., E. and W. edges.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T40N R61E R62E S 36 S 31 S 1 S 6 T39N 1984</p> <p>Bury the original cornerstone and set a steel fence post, $5\frac{1}{2}$ ft. long, alongside the iron post.</p> <hr/>	