

DEPENDENT RESURVEY OF A PORTION OF  
THE NORTH BOUNDARY,  
T. 8 N., R. 56 E., MDM, NEVADA

CHAINS

T 9N R56E  
S 33|S 34  
S 4|S 3  
T8N

1985

Deposit the steel rebar and reset the remains of the wooden post and set a steel fence post, 5½ ft. long, alongside the aluminum post.

From this corner, U.S.C. & G.S. triangulation station "S 33," monumented with a standard brass tablet, firmly set in concrete with brass tablet mkd. "S 33," bears N. 79° 44' W., 166.86 chs. dist.

DEPENDENT RESURVEY OF A PORTION OF  
THE SUBDIVISIONAL LINES,  
T. 8 N., R. 56 E., MDM, NEVADA

Reestablishment of the Survey Executed by  
A. G. Bateman and E. B. Monroe,  
U.S. Deputy Surveyors, in 1873.

From the cor. of secs. 1, 2, 11 and 12, monumented with a concrete monument, 3 ins. square, firmly set beneath the surface of the ground, with a wooden post, 4 ins. square, 4 ft. long, with illegible scribe marks visible, laying loose on the ground alongside. This is accepted as a careful and faithful perpetuation of the position of the original corner.

At the corner point

Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 8N R56E  
S 2|S 1  
S 11|S 12

1985

Deposit the concrete monument and reset the wooden post and set a steel fence post, 5½ ft. long, alongside the aluminum post.

N. 0° 01' E., bet. secs. 1 and 2.

Over gently rolling land, covered with scattered greasewood and shadscale.

30.50

Fence, bears N. 50° W. and S. 50° E.