

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,  
T. 8 N., R. 50 E., MDM, NEVADA

CHAINS	DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY, T. 8 N., R. 50 E., MOUNT DIABLO MERIDIAN, NEVADA
	<p>Reestablishment of the Survey Executed by D. H. Barker and W. W. Skinner, U.S. Deputy Surveyors, in 1875.</p> <hr/> <p>The cor. of Tps. 7 and 8 N., Rs. 50 and 51 E., monumented with a limestone, 20X9X2 ins., firmly set 6 ins. in the ground, plainly mkd. with 6 notches on N., S., E. and W. edges.</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>T8N R50E R51E S 36   S 31 S 1   S 6 T7N</p> </div> <p>1984</p> <p>Deposit the original cornerstone and set a steel fence post, 5½ ft. long, alongside the aluminum post.</p> <p>From this corner, U.S.G.S. triangulation station "L 129" (U.S.C. &amp; G.S. Bench Mark), monumented with a standard brass disk mkd. "L 129 1934" and firmly set in top of a concrete post, bears S. 66° 22' E., 75.64 chs. dist.</p> <p>S. 89° 59' W., bet. secs. 1 and 36.</p> <p>Over nearly level land, covered with scattered white sage and bunchgrass.</p> <p>24.30 Hot Creek Road, improved, bears ESE. and WNW.</p> <p>39.97 The ¼ sec. cor. of secs. 1 and 36, monumented with a limestone, 14X8X4 ins., firmly set 6 ins. in the ground, mkd. ¼ on N. face.</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p>