

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY
(RUBY VALLEY GUIDE MERIDIAN),
T. 8 N., R. 55 E., MDM, NEVADA

CHAINS	
40.04	<p>Set a steel fence post, 5½ ft. long, alongside the aluminum post.</p> <p>The cor. of secs. 13 and 24, monumented with an iron post, 3 ins. diam., with brass cap mkd. as described in the field notes of the resurvey of the Ruby Valley Guide Meridian, T. 8 N., Rs. 55 and 56 E., executed under Group No. 37. This post is rusted off at the surface, with the base section firmly set and the upper section lying alongside.</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T8N R55E R56E S 13 S 24 S 19</p> <p style="text-align: center;">1985</p> <p>Bury the original iron post and set a steel fence post, 5½ ft. long, alongside the aluminum post.</p>
<p>DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 8 N., R. 55 E., MOUNT DIABLO MERIDIAN, NEVADA</p>	
<p>Reestablishment of the Survey Executed by E. R. Bunbury, U.S. Transitman in 1915.</p>	
18.90	<p>From the cor. of secs. 24 and 25, on the E. bdy. of the Tp.</p> <p>S. 89° 58' W., bet. secs. 24 and 25.</p> <p>Over nearly level alkali lake bed.</p> <p>Leave alkali lake bed; enter small scattered hummocks, covered with scattered greasewood.</p>
25.60	Fence, bears N. 61° W. and S. 61° E.
39.95	<p>Point for the ¼ sec. cor. of secs. 24 and 25, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p>