

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY  
(RUBY VALLEY GUIDE MERIDIAN),  
T. 25 N., R. 55 E., MDM, NEVADA

CHAINS

Reestablishment of the Survey Executed by  
C. C. Tracy, U.S. Deputy Surveyor,  
in 1868.

From the cor. of Tps. 24 and 25 N., Rs. 55 and 56 E.,  
at proportionate distance; there is no remaining  
evidence of the original corner.

Set an aluminum post, 30 ins. long, 2½ ins. diam., 24  
ins. in the ground, with aluminum cap mkd.

T25N  
R55E R56E  
S 36 | S 31  
S 1 | S 6  
T24N

1984

Raise a mound of stone, 3 ft. base, 2 ft. high, S. of  
cor.

From this corner, the cor. of secs. 1, 6, 7 and 12,  
Tps. 24 N., Rs. 55 and 56 E., monumented with an  
aluminum post, 2½ ins. diam., firmly set and exposed 6  
ins. above ground, with aluminum cap mkd. as described  
in the field notes of the dependent resurvey of T. 24  
N., R. 55 E., (Ruby Valley Guide Meridian),  
concurrently resurveyed under this same Group, bears S.  
0° 40' W., 82.04 chs. dist.

N. 0° 40' E., bet. secs. 31 and 36.

Over rolling land, covered with medium sagebrush and  
scattered native grass.

41.02

Point for the ½ sec. cor. of secs. 31 and 36, at  
proportionate distance; there is no remaining evidence  
of the original corner.

Set an aluminum post, 30 ins. long, 2½ ins. diam., 24  
ins. in the ground, with aluminum cap mkd.

T25N  
R55E R56E  
½  
S 36 | S 31

1984

Raise a mound of stone, 2½ ft. base, 1½ ft. high, W. of  
cor.

82.04

Point for the cor. of secs. 25, 30, 31 and 36, at  
proportionate distance; there is no remaining evidence  
of the original corner.

Set an aluminum post, 30 ins. long, 2½ ins. diam., 24  
ins. in the ground, with aluminum cap mkd.