

DEPENDENT RESURVEY OF A PORTION OF
THE SUBDIVISIONAL LINES,
T. 25 N., R. 55 E., MDM, NEVADA

CHAINS 42.60	Wash, 20 lks. wide, 1 ft. deep, drains WNW.
69.00	Trail road, bears NE. and SW.
81.88	Point for the cor. of secs. 1, 2, 11 and 12, at proportionate distance; there is no remaining evidence of the original corner.
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.
	$\begin{array}{r} \text{T25N R55E} \\ \text{S } 2 \text{S } 1 \\ \hline \text{S } 11 \text{S } 12 \end{array}$
	1985
	Set a steel fence post, 5½ ft. long, alongside the aluminum post.
	<hr/> From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., firmly set showing 6 ins. above ground, with brass cap mkd. as described in the field notes of T. 25 N., R. 56 E., executed under Group No. 577.
	S. 88° 42' W., bet. secs. 1 and 12.
	Over gently rolling land, covered with crested wheatgrass.
40.12	Point for the ¼ sec. cor. of secs. 1 and 12, at proportionate distance; there is no remaining evidence of the original corner.
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.
	$\begin{array}{r} \text{T25N R55E} \\ \text{S } 1 \\ \hline \frac{1}{4} \text{ S } 12 \end{array}$
	1985
	Set a steel fence post, 5½ ft. long, alongside the aluminum post.
60.00	Trail road, bears ENE. and WSW.
80.24	The cor. of secs. 1, 2, 11 and 12.
	N. 0° 19' E., bet. secs. 1 and 2.
	Over gently rolling land, covered with crested wheatgrass and scattered sagebrush.
5.80	Wash, 10 lks. wide, 2 ft. deep, drains W.