

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 18 N., R. 63 E., MDM, NEVADA

CHAINS	
36.20	Wash, 20 lks. wide, 2 ft. deep, drains SW.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 30 and 31, NORTH, 0.2 lks. from the tangent.  Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with aluminum cap mkd.  <div style="text-align: center;">           T18N R63E  <math>\frac{1}{4}</math> <math>\frac{S\ 30}{S\ 31}</math>             1986         </div>
	Raise a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, N. of cor.
45.00	Leave medium densities of timber.
60.90	Trail road, bears NNE. and SSW.
76.60	Trail road, parallels fence.
76.80	Fence, bears N. $30\frac{1}{4}^{\circ}$ W. and S. $30\frac{1}{4}^{\circ}$ E.
78.87	Intersect the E. bdy. of sec. 36, T. 18 N., R. 62 E.  Point for the closing cor. of secs. 30 and 31, NORTH, 0.8 lks. from the tangent.  Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with aluminum cap mkd.  <div style="text-align: center;">           T18N            R62E R63E            S 36 <math>\frac{S\ 30}{S\ 31}</math> CC             1986         </div>
	Raise a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, E. of cor.  From this corner, the cor. of secs. 25 and 36, T. 18 N., R. 62 E., hereinbefore described, bears N. $0^{\circ} 08'$ W., 3.98 chs. dist.  Land, rolling. Soil, sandy clay loam. Undergrowth, scattered sagebrush, native grass and sparse cacti. Timber, medium to scattered juniper and pinon pine.
	Point for the W $\frac{1}{4}$ sec. cor. of sec. 31 is at 40.00 chs. in latitude from the closing cor. of secs. 30 and 31 and on the E. bdy. of sec. 36, T. 18 N., R. 62 E.