

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,
T. 2 N., R. 57 E., MDM, NEVADA

CHAINS	
	<p>Deposit the original cornerstone and set a steel fence post, 5½ ft. long, alongside the aluminum post.</p> <p>.....</p> <p>N. 0° 03' E., beginning new measurement.</p> <p>Over rolling land.</p>
1.57	The E ¼ sec. cor. of sec. 13, T. 2 N., R. 56 E., hereinafter described.
3.20	Ravine, drains ESE.
8.30	Spur, projects gently E.
18.90	Ravine, drains E.
25.90	Spur, projects E.
34.90	Ravine, drains ESE.
40.25	The cor. of secs. 7 and 18, monumented with an iron post, 2½ ins. diam., firmly set showing 6 ins. above ground, with a steel fence post set alongside, with a mound of stone E. of cor., and with brass cap mkd. as described in the field notes of T. 2 N., R. 57 E., executed under Group No. 551.
<p>SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 2 N., R. 56 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <p>.....</p>	
	<p>From the cor. of secs. 11, 12, 13 and 14, monumented with an iron post, 2½ ins. diam., firmly set showing 6 ins. above ground, with a steel fence post set alongside, with a mound of stone W. of cor., and with brass cap mkd. as described in the field notes of T. 2 N., R. 56 E., executed under Group No. 551.</p> <p>SOUTH, on a sectional guide meridian, bet. secs. 13 and 14.</p> <p>Over rolling mountainous land.</p>
0.40	Improved gravel road, bears WNW. and ESE.
1.30	Fence, bears ESE. and WNW.; 1.05 chs. dist. to corner of fences, from which fences bear ESE. and SSE.
9.90	Cottonwood Creek, 20 lks. wide, 1 ft. deep, course ESE.
20.00	Point for the N 1/16 sec. cor. of secs. 13 and 14.
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.