SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 2 N., R. 56 E., MDM, NEVADA

 	1. 2 AT, AT 30 DT, 12.1.3.1.
CHAINS	EAST, on a transit line describing the tangent, bet. secs. 13 and 24.
	Over rolling land.
13.70	Ravine, drains SE.
20.00	Point for the W 1/16 sec. cor. of secs. 13 and 24, NORTH, 0.1 lks. from the tangent.
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 25 ins. in the ground, with aluminum cap mkd.
	$W 1/16 \frac{S^{-}13}{S 24}$
	1986
	Set a steel fence post, 5½ ft. long, alongside the aluminum post.
40.00	Point for the ½ sec. cor. of secs. 13 and 24, NORTH, 0.2 lks. from the tangent.
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to top, with aluminum cap mkd.
	T2N R56E S-13 S-24
	1986
	Set a steel fence post, 5½ ft. long, alongside the aluminum post.
55.20	Trail road, bears N. and S.
56.40	Trail road, bears NW. and SE.
72.10	Cottonwood Creek, 20 1ks. wide, 1 ft. deep, course ESE.
79.57	Intersect the W. bdy. of sec. 18, T. 2 N., R. 57 E.
	Point for the closing cor. of secs. 13 and 24, NORTH, 0.8 lks. from the tangent.
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.
	T2N
	R56E R57E CC $\frac{S^-13}{S}$ S 18
	•
	1986
	Set a steel fence post, 5½ ft. long, alongside the aluminum post, and raise a mound of stone, 2½ ft. base, 1½ ft. high, W. of cor.