

DEPENDENT RESURVEY OF A PORTION OF
THE SUBDIVISIONAL LINES,
T. 39 N., R. 61 E., MDM, NEVADA

CHAINS	
	N. 89° 02' W., bet. secs. 25 and 36.
	Over rolling land, covered with scattered sagebrush.
0.40	Corner of fences, from which fences bear N. and W., along fence.
40.04	Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 36, determined latitudinally in a fence bearing E. and W., and longitudinally at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T39N R61E S 25 $\frac{1}{4}$ S 36
	1984
	Set a steel fence post, 5 $\frac{1}{2}$ ft. long, alongside the iron post.

	N. 89° 35' W., beginning new measurement.
	Over rolling land, along fence.
20.00	Corner of fences, from which fences bear N., E. and W.
40.04	The cor. of secs. 25, 26, 35 and 36.

	From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp., monumented with a ring spike, firmly set flush with the ground in an improved gravel road, bearing N. and S., mkd. as described in the field notes of the dependent resurvey of T. 39 N., R. 62 E., executed concurrently under this same Group.
	from which
	An iron post, firmly set showing 4 ins. above ground, bears N. 47 $\frac{1}{2}$ ° E., 66.1 lks. dist., in a corner of fences, bears N. and E., with brass cap mkd. as described in the field notes of the dependent resurvey of T. 39 N., R. 62 E., executed concurrently under this same Group. Remark the brass cap to read 43.6 FT.
	An iron post, firmly set showing 4 ins. above ground, bears S. 46° W., 66.1 lks. dist., in a fence bearing N. and S., with brass cap mkd. as described in the field notes of the dependent resurvey of T. 39 N., R. 62 E., executed concurrently under this same Group. Remark the brass cap to read 43.6 FT.