

DEPENDENT RESURVEY OF A PORTION OF
THE SUBDIVISIONAL LINES,
T. 40 N., R. 20 E., MDM, NEVADA

CHAINS

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to solid rock and in a mound of stone, 4 ft. base to top, with brass cap mkd.

¼ S 7
T40N R20E

1985

Deposit the unmarked cornerstone alongside the iron post.

N. 86° 22' W., beginning new measurement.

Over rolling mountainous land.

0.98

Point for the S ¼ sec. cor. of sec. 6, is on the N. bdy. of sec. 7, and at 40.00 chs. in departure from the cor. of secs. 5 and 6.

Set an iron post, 28 ins. long, 2½ ins. diam., on solid rock over a cross (X), in a mound of stone, 4 ft. base to top, with brass cap mkd.

T40N R20E
¼ S 6

1985

5.60

Ravine, drains SW.

35.77

The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp.

INDEPENDENT RESURVEY OF A PORTION OF
THE SUBDIVISIONAL LINES,
T. 40 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA

This Independent Resurvey Supersedes the Survey Executed by G. W. Garside, U.S. Deputy Surveyor, in 1878. A diligent search was made for the original corners and none were found.

From the cor. of secs. 4 and 9.

NORTH, along the E. bdy. of sec. 4.

Over rolling land, through scattered undergrowth.