

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 40 N., R. 20 E., MDM, NEVADA

CHAINS	
	<p>From this corner, a U.S.G.S. Bench Mark, monumented with a standard brass tablet, stamped "148 LRC 1972," firmly set in concrete, bears N. 68° 10' E., 21.39 chs. dist.</p>
68.40	Fence, bears NW. and SE.
69.50	Improved road, bears NW. and SE.
80.00	<p>Point for the 80 1/16 sec. cor. of sec. 3 only.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <math display="block">\begin{array}{r} 1/16   \\ S \quad 3   \\ \hline 80   \end{array}</math> <p>1985</p> </div> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p>
80.20	Fence, bears E. and W.
84.50	<p>Intersect the Eighth Standard Parallel North.</p> <p>Point for the closing cor. of secs. 2 and 3.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to solid rock and in a mound of stone, 4 ft. base to top, with brass cap mkd.</p> <div style="text-align: center;"> <math display="block">\begin{array}{r} T41N R20E \\ S \quad 35 \\ \hline S \quad 3   S \quad 2 \\ T40N R20E \\ C \quad C \end{array}</math> <p>1985</p> </div> <p>From this corner, the standard cor. of secs. 34 and 35, T. 41 N., R. 20 E., bears N. 88° 43' W., 6.77 chs. dist.</p> <p>Land, rolling. Soil, sandy clay and rocky. Undergrowth, sagebrush, greasewood and native grass.</p> <hr/> <p>Point for the N ¼ sec. cor. of sec. 2 is on the Eighth Standard Parallel North and at midpoint between the closing cors.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground to solid rock and in a mound of stone, 4 ft. base to top, with brass cap mkd.</p> <div style="text-align: center;"> <math display="block">\begin{array}{r} T41N R20E \\ \hline \frac{1}{4} S \quad 2 \\ T40N R20E \end{array}</math> <p>1985</p> </div>