DEPENDENT RESURVEY OF THE NORTH BOUNDARY, T. 27 N., R. 51 E., MDM, NEVADA

At the corner point Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. T28N R51E
ins. in the ground, with aluminum cap mkd. T28N R51E
1 <u>S 36</u>
<sup>1</sup> ∕ <sub>3</sub> <del>− 1</del> T27N
127 N
1985
Reset the original wooden post and set a steel fence post, 5½ ft. long, alongside the aluminum post.
N. 89° 58' E., beginning new measurement.
Over rolling land.
Bladed road, bears NE. and SW.
Intersect the W. bdy. of sec. 31, T. 28 N., R. 52 E.
Point for the closing cor. of Tps. 27 and 28 N., Rs. 51 E.
Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with aluminum cap mkd.
T28N
R51E R52E
$\operatorname{cc} \frac{\mathbf{S} \ 36}{\mathbf{S} \ 1}   \mathbf{S} \ 31$
T27N
1985
Set a steel fence post, $5\frac{1}{2}$ ft. long, alongside the
aluminum post.
From this corner, the original cor. of Tps. 27 and 28 N., Rs. 51 and 52 E., (as surveyed by W. M. Kearney) monumented with a wooden post, 3 ins. square, 24 ins. long, plainly scribed T28N on N. face and T27N on S. face, with 6 grooves on the N., S., E. and W. faces, firmly set in a mound of stone, bears N. 89° 58' E., 4.82 chs. dist. Add the marks AM and bury the post 6 ins. below the surface of the ground.
From this same corner, the cor. of Tps. 27 and 28 N., Rs. 52 E., hereinbefore described, bears S. 0° 01' W., 5.11 chs. dist.
DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES, T. 27 N., R. 51 E., MOUNT DIABLO MERIDIAN, NEVADA
1

89

FIELD NOTE PAPER