DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY, T. 27 N., R. 52 E., MDM, NEVADA

	T. 27 N., R. 52 E., MDM, NEVADA
CHAINS	
40.12	The ½ sec. cor. of secs. 6 and 31, monumented with the decayed remains of a wooden post, loosely set in a mound of earth, with illegible scribe marks visible.
	At the corner point
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.
	T28N R52E
	$\frac{1}{4}$ $\frac{\frac{s}{31}}{\frac{1}{5}}$
	T27N
	1985
	Reset the remains of the original wooden post and set a steel fence post, 5½ ft. long, alongside the aluminum post.
	N. 89° 52' W., beginning new measurement.
	Over gently rolling land.
12.60	Bladed road, parallels old railroad bed.
13.60	Old abandoned railroad bed, bears N. 43° E. and S. 43° W.
39.35	The cor. of Tps. 27 and 28 N., Rs. 52 E., monumented with an aluminum post, $2\frac{1}{2}$ ins. diam., firmly set exposed 6 ins. above ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 27 N., R. 51 E., executed concurrently under this same Group.
	DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 27 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA
	Reestablishment of a Portion of the Survey Executed by O. A. Palmer, U.S. Deputy Surveyor, in 1870, and Resurvey of a Portion of the Survey Executed by U.S. Cadastral Engineer G. W. Ridgway and U.S. Surveyor C. S. Swanholm, in 1924 and 1926.
	The ½ sec. cor. of secs. 34 and 35, monumented with an iron post, 1 in. diam., firmly set in a mound of stone and exposed 9 ins. above ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines of T. 27 N., R. 52 E., executed under Group No. 111.
	Remark the brass cap to read: