

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,  
T. 29 N., R. 51 E., MDM, NEVADA

CHAINS	<p>Reestablishment of a Portion of the Survey Executed by W. M. Kearney, U.S. Deputy Surveyor, in 1909.</p>								
	<p>The cor. of Tps. 28 and 29 N., Rs. 51 and 52 E., monumented with a wooden post, 4 ins. square, 30 ins. long, loosely set in a mound of earth, with illegible scribe marks visible.</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>T29N R51E R52E S 36   S 31 S 1   S 6</p> </div> <p>T28N</p> <p>1985</p> <p>Reset the original wooden post and set a steel fence post, 5½ ft. long, alongside the aluminum post and raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.</p> <p>N. 89° 55' W., along the S. bdy. of sec. 36.</p> <p>Over gently rolling land, covered with sagebrush, native grass and scattered juniper.</p> <tr> <td>35.77</td><td>The N ¼ sec. cor. of sec. 1, T. 28 N., R. 51 E., hereinafter described.</td></tr> <tr> <td>39.98</td><td> <p>The S ¼ sec. cor. of sec. 36, T. 29 N., R. 51 E., monumented with limestone, 24X12X6 ins., firmly set 12 ins. in the ground and plainly mkd. ¼ on N. face.</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>T29N R51E ¼ S 36</p> </div> <p>T28N</p> <p>1985</p> <p>Deposit the original cornerstone and set a steel fence post, 5½ ft. long, alongside the aluminum post.</p> <p>N. 89° 51' W., beginning new measurement.</p> <p>Over gently rolling land.</p> <tr> <td>17.10</td><td>Enter rolling land, with scattered juniper.</td></tr> <tr> <td>35.75</td><td>The closing cor. of secs. 1 and 2, T. 28 N., R. 51 E., hereinafter described.</td></tr> </td></tr>	35.77	The N ¼ sec. cor. of sec. 1, T. 28 N., R. 51 E., hereinafter described.	39.98	<p>The S ¼ sec. cor. of sec. 36, T. 29 N., R. 51 E., monumented with limestone, 24X12X6 ins., firmly set 12 ins. in the ground and plainly mkd. ¼ on N. face.</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>T29N R51E ¼ S 36</p> </div> <p>T28N</p> <p>1985</p> <p>Deposit the original cornerstone and set a steel fence post, 5½ ft. long, alongside the aluminum post.</p> <p>N. 89° 51' W., beginning new measurement.</p> <p>Over gently rolling land.</p> <tr> <td>17.10</td><td>Enter rolling land, with scattered juniper.</td></tr> <tr> <td>35.75</td><td>The closing cor. of secs. 1 and 2, T. 28 N., R. 51 E., hereinafter described.</td></tr>	17.10	Enter rolling land, with scattered juniper.	35.75	The closing cor. of secs. 1 and 2, T. 28 N., R. 51 E., hereinafter described.
35.77	The N ¼ sec. cor. of sec. 1, T. 28 N., R. 51 E., hereinafter described.								
39.98	<p>The S ¼ sec. cor. of sec. 36, T. 29 N., R. 51 E., monumented with limestone, 24X12X6 ins., firmly set 12 ins. in the ground and plainly mkd. ¼ on N. face.</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>T29N R51E ¼ S 36</p> </div> <p>T28N</p> <p>1985</p> <p>Deposit the original cornerstone and set a steel fence post, 5½ ft. long, alongside the aluminum post.</p> <p>N. 89° 51' W., beginning new measurement.</p> <p>Over gently rolling land.</p> <tr> <td>17.10</td><td>Enter rolling land, with scattered juniper.</td></tr> <tr> <td>35.75</td><td>The closing cor. of secs. 1 and 2, T. 28 N., R. 51 E., hereinafter described.</td></tr>	17.10	Enter rolling land, with scattered juniper.	35.75	The closing cor. of secs. 1 and 2, T. 28 N., R. 51 E., hereinafter described.				
17.10	Enter rolling land, with scattered juniper.								
35.75	The closing cor. of secs. 1 and 2, T. 28 N., R. 51 E., hereinafter described.								