

DEPENDENT RESURVEY OF A PORTION OF
THE SUBDIVISIONAL LINES,
T. 28 N., R. 51 E., MDM, NEVADA

CHAINS		
40.13	<p>N. 0° 01' E., beginning new measurement.</p> <p>Over rolling land.</p> <p>The cor. of secs. 23, 24, 25 and 26, monumented with the decayed remains of a wooden post, loosely set in a mound of earth, with illegible scribe marks visible.</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>T28N R51E</p> <p>S 23 S 24</p> <p>S 26 S 25</p> </div> <p style="text-align: center;">1985</p> <p>Reset the original wooden post and set a steel fence post, 5½ ft. long, alongside the aluminum post.</p>	
39.90	<p>S. 89° 46' E., bet. secs. 24 and 25.</p> <p>Over rolling land, covered with sagebrush and native grass.</p> <p>The ¼ sec. cor. of secs. 24 and 25, monumented with a wooden post, 3 ins. square, 24 ins. long, firmly set 10 ins. in the ground and plainly mkd. ¼ on N. face.</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>T28N R51E</p> <p>¼ S 24</p> <p>¼ S 25</p> </div> <p style="text-align: center;">1985</p> <p>Reset the original wooden post and set a steel fence post, 5½ ft. long, alongside the aluminum post.</p>	
35.67	<p>S. 89° 50' E., beginning new measurement.</p> <p>Over rolling land.</p> <p>Intersect the W. bdy. of sec. 19, T. 28 N., R. 52 E.</p> <p>Point for the closing cor. of secs. 24 and 25.</p>	