

DEPENDENT RESURVEY OF A PORTION OF  
THE SUBDIVISIONAL LINES,  
T. 28 N., R. 51 E., MDM, NEVADA

CHAINS	
	<p>Deposit the original cornerstone alongside the aluminum post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p>
	<p>S. 89° 52' E., bet. secs. 12 and 13.</p>
	<p>Over rolling land, covered with sagebrush and native grass.</p>
30.40	<p>Ridge, bears SE. and NW.</p>
40.00	<p>The <math>\frac{1}{4}</math> sec. cor. of secs. 12 and 13, monumented with a wooden post, 3 ins. square, 40 ins. long, firmly set in a mound of earth and dimly mkd. <math>\frac{1}{4}</math> on N. face.</p>
	<p>At the corner point</p>
	<p>Set an aluminum post, 30 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p>
	<p style="text-align: center;">T28N R51E  <math>\frac{1}{4}</math> <math>\frac{S}{S}</math> <math>\frac{12}{13}</math>  1985</p>
	<p>Reset the original wooden post and set a steel fence post, 5<math>\frac{1}{2}</math> ft. long, alongside the aluminum post.</p>
	<p>S. 89° 47' E., beginning new measurement.</p> <p>Over rolling land.</p>
35.71	<p>Intersect the W. bdy. of sec. 7, T. 28 N., R. 52 E.</p>
	<p>Point for the closing cor. of sec. 12, T. 28 N., R. 51 E.</p>
	<p>Set an aluminum post, 30 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p>
	<p style="text-align: center;">T28N   R51E   CC <math>\frac{S}{S}</math> <math>\frac{12}{12}</math>  1985</p>
	<p>Set a steel fence post, 5<math>\frac{1}{2}</math> ft. long, alongside the aluminum post.</p>
	<p>From this corner, the SW. cor. of sec. 7, T. 28 N., R. 52 E., monumented with an aluminum post, 2<math>\frac{1}{2}</math> ins. diam., firmly set showing 6 ins. above ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of T. 28 N., R. 52 E., executed concurrently under this same Group, bears S. 0° 03' W., 4.75 chs. dist.</p>
37.30	<p>The NE. cor. of sec. 13, on the E. bdy. of the Tp., hereinbefore described.</p>