

DEPENDENT RESURVEY OF A PORTION OF
THE SUBDIVISIONAL LINES,
T. 28 N., R. 51 E., MDM, NEVADA

CHAINS

36.80

The SE. cor. of sec. 1, on the E. bdy. of the Tp.,
hereinbefore described.

Point for the E $\frac{1}{4}$ sec. cor. of sec. 12, established at
the intersection of the E-W center line of sec. 12, and
on the W. bdy. of sec. 7, T. 28 N., R. 52 E.

Set an aluminum post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24
ins. in the ground, with aluminum cap mkd.

T28N
R51E R52E
 $\frac{1}{4}$ |
S 12 |

1985

Set a steel fence post, 5 $\frac{1}{2}$ ft. long, alongside the
aluminum post.

From this corner, the amended monument for the $\frac{1}{4}$ sec.
cor. of sec. 12, hereinbefore described, bears S. 89°
47' E., 1.21 chs. dist.

From this same corner, the $\frac{1}{4}$ sec. cor. of secs. 11 and
12, hereinbefore described, bears N. 89° 47' W.

From the cor. of secs. 1, 2, 11 and 12.

N. 0° 02' E., bet. secs. 1 and 2.

Over rolling land, covered with sagebrush and scattered
juniper.

28.30

Wash, 20 lks. wide, 2 ft. deep, drains ENE.

39.93

The $\frac{1}{4}$ sec. cor. of secs. 1 and 2, monumented with a
limestone, 24X16X8 ins., firmly set 10 ins. in the
ground and plainly mkd. $\frac{1}{4}$ on W. face.

At the corner point

Set an aluminum post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24
ins. in the ground, with aluminum cap mkd.

T28N R51E
 $\frac{1}{4}$
S 2 | S 1

1985

Deposit the original cornerstone and set a steel fence
post, 5 $\frac{1}{2}$ ft. long, alongside the aluminum post.