

233

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
T. 39 N., R. 19 E., MDM, NEVADA

CHAINS

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T39N
R19E | R20E
¼ |
S 1 |

1985

Deposit the original cornerstone alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

DEPENDENT RESURVEY OF A PORTION OF
THE SUBDIVISIONAL LINES,
T. 39 N., R. 19 E., MDM, NEVADA

Reestablishment of the Survey Executed by
U.S. Deputy Surveyors C. F. Putnam and W. F. Benson
in 1880

From the cor. of secs. 1 and 12, on the E. bdy. of the
Tp.

S. 89° 54' W., bet. secs. 1 and 12.

Over rolling mountainous land, through scattered
sagebrush.

34.00 Trail road, bears NE. and SW.

34.50 Fence, bears NE. and SW.

40.08 Point for the ¼ sec. cor. of secs. 1 and 12, at
proportionate distance; there is no remaining evidence
of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T39N R19E
S 1
¼ S 12

1985

Raise a mound of stone, 3 ft. base, 2 ft. high, N. of
cor.

80.16 The cor. of secs. 1, 2, 11 and 12, monumented with an
unmarked basalt stone, 12X10X6 ins., firmly set in a
mound of stone. This point correlates well with other
existing original corners and is accepted as the best
available evidence of the position of the original
corner.