

DEPENDENT RESURVEY OF A PORTION OF
THE SUBDIVISIONAL LINES,
T. 39 N., R. 19 E., MDM, NEVADA

CHAINS	
	<p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T39N R19E S 2 S 1 <u>S 11 S 12</u></p> <p style="text-align: center;">1985</p> <p>Deposit the unmarked basalt stone and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p>
	<p>N. 0° 53' W., bet. secs. 1 and 2.</p>
	<p>Over rolling mountainous land, covered with scattered sagebrush and buckbrush.</p>
38.50	<p>Ravine, drains SW.</p>
39.00	<p>Point for the ¼ sec. cor. of secs. 1 and 2, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground to solid rock and in a mound of stone, 4 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T39N R19E S 2 S 1 ¼</p> <p style="text-align: center;">1985</p>
78.00	<p>Point for the 80 1/16 sec. cor. of secs. 1 and 2, at proportionate distance.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">1/16 S 2 S 1 80</p> <p style="text-align: center;">1985</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p>
97.50	<p>Point for the 100 1/16 sec. cor. of secs. 1 and 2, at proportionate distance.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground to solid rock and in a mound of stone, 4 ft. base to top, with brass cap mkd.</p>