

DEPENDENT RESURVEY OF A PORTION OF
THE SUBDIVISIONAL LINES,
T. 39 N., R. 19 E., MDM, NEVADA

CHAINS		
	Over rolling mountainous land, covered with scattered sagebrush and buckbrush.	
29.50	Wash, 10 lks. wide, 2 ft. deep, drains SSW.	
39.80	Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 11, at proportionate distance; there is no remaining evidence of the original corner.	
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.	
	<p style="text-align: center;">T39N R19E S 2 $\frac{1}{4}$ S TT</p> <p style="text-align: center;">1985</p>	
	Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.	
45.50	Fence, bears N. and S.	
79.60	The cor. of secs. 2, 3, 10 and 11, monumented with an unmarked ironstone, 15X10X6 ins., firmly set in a mound of stone. This point correlates well with other existing original corners and is accepted as the best available evidence of the position of the original corner.	
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.	
	<p style="text-align: center;">T39N R19E S 3 S 2 S 10 S 11</p> <p style="text-align: center;">1985</p>	
	Deposit the original cornerstone alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.	
	<hr/>	
	N. $1^{\circ} 00'$ W., bet. secs. 2 and 3.	
	Over rolling mountainous land, covered with scattered sagebrush and buckbrush.	
39.54	Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 3, at proportionate distance; there is no remaining evidence of the original corner.	
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.	
	<p style="text-align: center;">T39N R19E $\frac{1}{4}$ S 3 S 2</p> <p style="text-align: center;">1985</p>	