

DEPENDENT RESURVEY OF A PORTION OF  
THE SUBDIVISIONAL LINES,  
T. 39 N., R. 19 E., MDM, NEVADA

CHAINS	
	<p>N. 0° 25' W., bet. secs. 3 and 4.</p> <p>Over rolling mountainous land, covered with scattered sagebrush.</p>
27.30	Mountain View Creek, 10 lks. wide, 1 ft. deep, course E.
39.36	<p>The <math>\frac{1}{4}</math> sec. cor. of secs. 3 and 4, monumented with an unmarked ironstone, 28X12X4 ins., firmly set in a mound of stone. This point correlates well with other existing original corners and is accepted as the best available evidence of the position of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to solid rock and in a mound of stone, 4 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T39N R19E S 3½ S 2 1985</p> <p>Deposit the unmarked cornerstone alongside the iron post.</p> <hr/> <p>N. 0° 36' W., beginning new measurement.</p>
39.82	<p>Point for the 80 1/16 sec. cor. of secs. 3 and 4, at proportionate distance.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground to solid rock and in a mound of stone, 4 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">1/16 S 4½ S 3 80 1985</p>
59.73	<p>Point for the 100 1/16 sec. cor. of secs. 3 and 4, at proportionate distance.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">1/16 S 4½ S 3 100 1985</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p>
67.00	Trail road, bears SSE. and NNW.
72.50	Wash, 30 lks. wide, 1 ft. deep, drains SSE.
79.64	Point for the 120 1/16 sec. cor. of secs. 3 and 4, at proportionate distance.