

DEPENDENT RESURVEY OF A PORTION OF
THE SUBDIVISIONAL LINES,
T. 39 N., R. 19 E., MDM, NEVADA

CHAINS

Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to solid rock and in a mound of stone, 4 ft. base to top, with brass cap mkd.

T39N R19E
S 6 | S 5
S 7 | S 8

1985

Deposit the unmarked cornerstone alongside the iron post.

S. 89° 26' W., bet. secs. 6 and 7.

Over mountainous land, covered with scattered sagebrush, mahogany, quaking aspen and serviceberry.

29.60 Wash, 20 lks. wide, 3 ft. deep, drains N.

30.30 Trail road, bears N. and S.

38.68 Point for the ¼ sec. cor. of secs. 6 and 7, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to top, with brass cap mkd.

T39N R19E
S 6
¼ S 7

1985

77.16 The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., firmly set showing 6 ins. above ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 39 N., R. 18 E., executed concurrently under this same Group.

From the cor. of secs. 5, 6, 7 and 8.

N. 1° 15' E., bet. secs. 5 and 6.

Over mountainous land, covered with scattered sagebrush, bunchgrass, mahogany and quaking aspen.

40.09 The ¼ sec. cor. of secs. 5 and 6, monumented with an unmarked iron stone, 18X12X4 ins., firmly set in a mound of stone. This point correlates well with other existing original corners and is accepted as the best available evidence of the position of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 8 ins. in the ground to solid rock and in a mound of stone, 4 ft. base to top, with brass cap mkd.