DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 40 N., R. 18 E., MDM, NEVADA

	1. 40 N., K. 18 E., MUM, NEVADA
CHAINS	N. 0° 01' W., bet. secs. 25 and 26.
	Over mountainous land, through scattered sagebrush, bunchgrass and juniper.
39.94	The 1 sec. cor. of secs. 25 and 26, monumented with an iron post, 1 in. diam., firmly set in a mound of stone, with brass cap mkd. as described in the field notes of the survey of the subdivisional lines of T. 40 N., R. 18 E., executed under Group No. 5. Add the marks T40N R18E 1985 to the brass cap.
	N. 0° 03' E., beginning new measurement.
	Over mountainous land.
40.03	The cor. of secs. 23, 24, 25 and 26, monumented with an iron post, 2 ins. diam., firmly set and exposed 6 ins. above the ground, with brass cap mkd. as described in the field notes of the survey of the subdivisional lines of T. 40 N., R. 18 E., executed under Group No. 5. Add the marks 1985 to the brass cap.
	S. 89° 40' E., bet. secs. 24 and 25.
	Over mountainous land, through scattered sagebrush, bunchgrass and juniper.
26.52	Intersect the W. bdy. of sec. 30, T. 40 N., R. 19 E.
	Point for the closing cor. of secs. 24 and 25, established at the intersection of the line between secs. 24 and 25, of the 1911 survey and on the W. bdy. of sec. 30, T. 40 N., R. 19 E., dependently resurveyed concurrently under this same Group.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T40N T40N CC S 24 S 30 S 25 R19E
	1985
-	
	Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
	From this corner, the cor. of secs. 19 and 30, T. 40 N., R. 19 E., monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set in a mound of stone, with brass cap mkd. as described in the field notes of the dependent resurvey of the W. bdy. of T. 40 N., R. 19 E., executed concurrently under this same Group, bears N. 0° 34' E., 6.03 chs. dist.