

INDEPENDENT RESURVEY OF A PORTION OF  
THE SUBDIVISIONAL LINES,  
T. 40 N., R. 19 E., MDM, NEVADA

<p>CHAINS</p> <p>64.40</p> <p>82.54</p>	<p>Set an iron post, 28 ins. long, 2½ ins. diam., on solid rock over a cross (X), in a mound of stone, 5 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T40N R19E S 3½ S 2 1984</p> <p>Set a steel fence post, 5½ ft. long, alongside the iron post.</p> <p>Fence, bears E. and W.</p> <p>Intersect the Eighth Standard Parallel North.</p> <p>Point for the closing cor. of secs. 2 and 3.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground to solid rock and in a mound of stone, 4 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T41N R19E S 35 S 3½ S 2 CIC T40N R19E 1984</p> <p>From this corner, the standard cor. of secs. 34 and 35, T. 41 N., R. 19 E., hereinbefore described, bears WEST, 1.51 chs. dist.</p> <hr/> <p>Point for the N ¼ sec. cor. of sec. 2, is at midpoint between the closing cors. and on the Eighth Standard Parallel North.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 8 ins. in the ground to solid rock and in a mound of stone, 5 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T41N R19E ¼ S 2 T40N R19E 1985</p> <p>From this corner, the standard ¼ sec. cor. of sec. 35, T. 41 N., R. 19 E., hereinbefore described, bears WEST, 1.11 chs. dist.</p> <hr/> <p>From the cor. of secs. 3, 4, 9 and 10.</p> <p>N. 0° 02' W., bet. secs. 3 and 4.</p> <p>Over rolling land, through scattered sagebrush and greasewood.</p>
---	---