345

INDEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 40 N., R. 19 E., MDM, NEVADA

CHAINS

From this corner, the standard & sec. cor. of sec. 33, T. 41 N., R. 19 E., hereinbefore described, bears WEST, 1.73 chs. dist.

From the cor. of secs. 5 and 6.

N. 0° 04' W., bet. secs. 5 and 6.

Over rolling land, through scattered sagebrush.

38.56

Point for the $\frac{1}{4}$ sec. cor. of secs. 5 and 6, established at 40.00 chs. in departure from the closing cor. of secs. 5 and 6.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T40N R19E S 6|S 5

1985

Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

78.56

Intersect the Eighth Standard Parallel North.

Point for the closing cor. of secs. 5 and 6.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T41N R19E S 32 S 61S 5 CIC T40N R19E

1985

Set a steel fence post, $5\frac{1}{2}$ ft. long, alongside the iron post.

From this corner, the standard cor. of secs. 31 and 32, T. 41 N., R. 19 E., hereinbefore described, bears N. 89° 59' W., 1.84 chs. dist.

Point for the N $\frac{1}{4}$ sec. cor. of sec. 5, is at midpoint between the closing cors. and on the Eighth Standard Parallel North.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T41N R19E

¼ S 5 T40N R19E

1985