

371

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,  
T. 14 N., R. 20 E., MDM, NEVADA

CHAINS

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,  
T. 14 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey Executed by  
U.S. Deputy Surveyor J. S. Lawson, in 1861  
and the Dependent Resurvey Executed by  
Cadastral Surveyor D. A. Cannon, in 1963.

The cor. of secs. 4, 5, 32 and 33, identical with Angle Point 5, Parcel A, T. 15 N., R. 20 E., monumented with a brass tablet, 2 ins. diam., firmly set in a 3 ins. diam. iron pipe, filled with concrete, showing 22 ins. above ground, with brass tablet mkd. as described in the field notes of T. 14 N., R. 20 E., executed under Group No. 406.

N. 89° 49' W., bet. secs. 5 and 32.

Over nearly level land, covered with medium sagebrush, scattered rabbitbrush and native grass.

- 5.90 Bigelow Drive, paved, bears NNW. and SSE.
- 6.785 Angle Point 4, Parcel A, T. 15 N., R. 20 E., monumented with an aluminum post, 2½ ins. diam., firmly set showing 6 ins. above ground, with aluminum cap mkd. as described in the field notes of T. 15 N., R. 20 E., executed concurrently under this same Group.
- 20.085 Point for the E 1/16 sec. cor. of secs. 5 and 32.
- Set an aluminum post, 30 ins. long, 2½ ins. diam., 30 ins. flush with the ground, with aluminum cap mkd.
- E 1/16  $\frac{S\ 32}{S\ 5}$
- 1985
- 21.637 Intersect line 4-1, Parcel B, from which Angle Point 4, Parcel B, monumented with a rebar, 5/8 in. diam., firmly set flush in ground, with aluminum cap mkd. as described in the field notes of T. 15 N., R. 20 E., executed concurrently under this same Group, bears S. 26° 54' W., 0.213 chs. dist.
- 22.122 Intersect line 3-4, Parcel B, from which Angle Point 4, Parcel B, monumented with a rebar, 5/8 in. diam., firmly set flush in ground, with aluminum cap mkd. as described in the field notes of T. 15 N., R. 20 E., executed concurrently under this same Group, bears S. 63° 46' E., 0.433 chs. dist.
- 40.17 The ¼ sec. cor. of secs. 5 and 32, monumented with a copper-coated steel stake, ½ in. diam., firmly set 18 ins. below the surface of the Stewart Indian School track, with brass cap, 1½ ins. diam., mkd. as described in the field notes of T. 14 N., R. 20 E., executed under Group No. 406.