

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,
T. 13 N., R. 19 E., MDM, NEVADA

CHAINS

Reestablishment of the Survey Executed by
C. S. Swanholm, R. F. Wilson, G. M. Litz and
W. McConkie, Cadastral Engineers,
in 1939 - 1950.

The cor. of secs. 25, 30, 31 and 36, monumented with an iron pipe, 2 ins. diam., firmly set, projecting 5 ins. above ground, and in a mound of stone, 3 ft. base, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 13 N., R. 18 E., executed under Group No. 245. Add the marks 1985 to the brass cap, from which the 1861 bearing trees

A red fir, 42 ins. diam., bears N. 88° E., 76 lks. dist., with healed blaze. (1939 Record N. $87\frac{1}{4}^{\circ}$ E.) (1861 Record 80 lks. dist.)

A red fir, 35 ins. diam., bears S. 61° E., 150 lks. dist., with healed blaze. (1939 Record S. 62° E., 160 lks.) (1861 Record 152 lks. dist.)

A red fir, 19 ins. diam., bears S. 35° W., 153 lks. dist., with healed blaze. (1939 Record S. 36° W., 154 lks.) (1861 Record S $34^{\circ} 45'$ W., 153 lks. dist.)

A red fir, 30 ins. diam., bears N. 71° W., 83 lks. dist., mkd. 13N 18E 25 BT and a chaining notch on open blazes. (1861 Record a pine, N. $69\frac{1}{2}^{\circ}$ W., 79 lks., 1939 Record a pine, N. $69\frac{1}{2}^{\circ}$ W., 22 lks.)

and the 1939 bearing trees

A pine, 15 ins. diam., bears N. $84\frac{1}{2}^{\circ}$ E., 66 lks. dist., with illegible marks visible on partially healed blaze. (Record a fir, N. 85° E., 67 lks.)

A fir, 21 ins. diam., bears S. 88° E., 146 lks. dist., with healed blaze. (Record S. 79° E., 145 lks.)

A fir, 14 ins. diam., bears S. 55° W., 137 lks. dist., with healed blaze. (Record S. $55\frac{1}{4}^{\circ}$ W., 138 lks.)

A fir, $15\frac{1}{2}$ ins. diam., bears N. 66° W., 21 lks. dist., with healed blaze. (Record N. $45\frac{1}{2}^{\circ}$ W., 22 lks.)

Corner is located on rocky E. slope.

N. $0^{\circ} 18'$ E., bet. secs. 25 and 30.

Over mountainous land.

19.59

Point for the S $1/16$ sec. cor. of secs. 25 and 30.

Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground with a magnet at base, and in a collar, of stone, $2\frac{1}{2}$ ft. base, to top, with brass cap mkd.