

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 38 N., R. 52 E., MDM, NEVADA

CHAINS	
	<p>N. 88° 52' W., bet. secs. 6 and 31.</p> <p>Over rolling mountainous land, covered with sagebrush, buckbrush and native grass.</p>
5.10	Lake Creek, 20 lks. wide, 3 ft. deep, course ENE.
6.80	Trail road, bears ENE. and WSW.
39.98	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 6 and 31, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 30 ins. long, 2$\frac{1}{2}$ ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> $\begin{array}{r} \text{T38N R52E} \\ \text{S } 31 \\ \frac{1}{4} \text{ S } 6 \\ \text{T37N} \end{array}$ <p>1986</p> <p>Set a steel fence post, 5$\frac{1}{2}$ ft. long, alongside the aluminum post.</p>
78.50	Lake Creek, 20 lks. wide, 2 ft. deep, course SE.
79.56	<p>The cor. of Tps. 37 and 38 N., Rs. 51 and 52 E., monumented with an unmarked trap stone, 16X10X6 ins., firmly set in a mound of stone. This trap stone correlates well with other existing original corners and is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2$\frac{1}{2}$ ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> $\begin{array}{r} \text{T38N} \\ \text{R51E R52E} \\ \text{S } 36 \text{S } 31 \\ \text{S } 1 \text{S } 6 \\ \text{T37N} \end{array}$ <p>1986</p> <p>Deposit the unmarked stone and set a steel fence post, 5$\frac{1}{2}$ ft. long, alongside the aluminum post and raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.</p>